

# CTB Windows

## Commercial Thermal-Break Aluminum Window DATA SHEET

HIGH-PERFORMANCE COMMERCIAL GRADE ALUMINUM WINDOW  
 DESIGNED FOR THE COMMERCIAL MARKET  
 INSULATED GLASS WITH 100% THERMALLY-BROKEN FRAME AND SASH  
 FULL-PERIMETER WEATHER STRIPPING FOR ALL SASHES

### Physical Characteristics

<b>STYLES - 500 SHS</b>	Horizontal Single Sliders with Step-Saver Frame
<b>510 HS</b>	Horizontal Single Sliders with Nailing Flange
<b>510 HSJ</b>	Horizontal Single Slider with attached J-Trim 1-1/8" depth
<b>510 HT</b>	Horizontal Three Panel End Sliders
<b>520 VSH</b>	Vertical Single Hungs with Nailing Flange
<b>520 SVSH</b>	Vertical Single Hung with Step-Saver Trim attached
<b>520 VSHJ</b>	Vertical Single Hung with attached J-Trim 1-1/8" depth
<b>520 VSHS</b>	Special Vertical Single Hung (1/3 Slider, 2/3 fixed) with Nailing Flange
<b>540 FL</b>	Fixed Lite Picture Window with Nailing Flange
<b>540 FLJ</b>	Fixed Lite Picture Window with attached J-Trim 1-1/8" depth
<b>540 SFL</b>	Fixed Lite Picture Window with Step Saver Trim attached

**COLORS** - Polar White, Bronze, Chocolate and Hickory Moss. Exposed surfaces are covered with a polyester paint finish.

**GLASS** - 5/8" Double Sealed Insulated Glass

Options Available: Grids  
 Tinted  
 Tempered Safety Glass

**SIZES** - Standard Sizes are:

	Out to Out Measurements		Out to Out Measurements
2030	23-1/2" x 35-1/2"	3060	35-1/2" x 71-1/2"
2040	23-1/2" x 47-1/2"	4030	47-1/2" x 35-1/2"
2050	23-1/2" x 59-1/2"	4040	47-1/2" x 47-1/2"
3030	35-1/2" x 35-1/2"	4050	47-1/2" x 59-1/2"
3040	35-1/2" x 47-1/2"	4060	47-1/2" x 71-1/2" (VHS or FL only, not available in a single HS unit)
3050	35-1/2" x 59-1/2"	5040	59-1/2" X 47-1/2" (HS or FL only, not available in a single VSH unit)

Special Sizes can be ordered.\* Multiple windows can be mullioned together using special mullion strips.

Due to Plyco Corporation's ongoing commitment to product improvement, we reserve the right to change without notice, product specifications and availability.