



Series 66

DATA SHEETS

INSULATED WALK DOOR, PRE-HUNG WITH HEADER AND THRESHOLD
PRE-HUNG 4 WAY UNIVERSAL IS STANDARD

Physical Characteristics

- SIZES -** **Single Doors:** Width for single doors is limited to 4' (40), height is limited to 7' (70). Doors can be made in any size within these limitations.
- Double Doors:** Double doors are not recommended in this door series.
- COLORS -** Mil-finish jamb and panel perimeter with Polar White embossed skin.
- JAMB -** 1-7/8" "L" type, mil-finish, aluminum jamb with nailing fin. Header and threshold are formed with jamb material and has wool pile seals. Jamb is available in mil-finish only.
- HINGES -** 6" aluminum hinges are standard. Three hinges per panel.
- DOOR PANEL -** Aluminum frame surrounds the panel and captures the embossed steel skin. 1-1/2" panel has a polyurethane injected foam core. Standard comes bred for lockset at 2-3/4" setback with rectangular latch plate prep.
- BLOCKING -** Blocked and drilled for lockset standard. Closer blocking is optional. When latch guard is ordered, door is blocked and guard is installed over lockset. When deadbolt is ordered, door is blocked and prepped for deadbolt.
- SKIN TYPE -** Panels under 48" (40) in width - 32 gauge embossed Polar white steel is standard. Panels 48" (40) in width - 29 gauge embossed Polar white steel is standard. Optional skins available: pebbled white fiberglass; embossed white aluminum.
- THRESHOLD -** Aluminum thresholds are used with this door series. Standard is not handicapped approved.
- LITE KITS -** Lites often requested are:
- 1 LA 20x24 no grids
 - 1 LU 4x 48 no grids.
- Additional lite kits are available, see the accessory pages for other lite sizes.
- HARDWARE -** See accessory pages for listing of hardware available.