



AND Windows

Andersen 100 Series Window

DATA SHEET

ENERGY SAVING & ENVIRONMENTALLY FRIENDLY WINDOW
 FIBREX MATERIAL FRAME - 40% RECYCLED FIBER - LEED QUALIFIED
 INSULATED GLASS WITH LO-E AND ARGON FILL
 3-1/4" FRAME DEPTH WITH NAILING FLANGE 1-3/8" SETBACK

Physical Characteristics

- STYLES - HS** Horizontal Single Slider with Nailing Flange
- VSH** Vertical Single Hung with Nailing Flange
- VSH2** (Special Order) Vertical single Hung Double with Nailing Flange
- CA L or R** Casement Single (Left or Right Swing) with Nailing Flange
- CA2** (Special Order) Casement Double with Nailing Flange
- FL** (Special Order) Fixed Lite Picture Window with Nailing Flange
- CT** Half-Circular Top

COLORS - Stock Exterior White, Stock Exterior Hickory Moss. All Windows - Interior White

GLASS - 5/8" Double Sealed Insulated Glass - Lo-E with Argon Fill is Standard.

Options Available: Grids Color Exterior, White Interior.
 Field mulling kit.

SIZES - Standard Sizes are

| | HS Out to Out Measurements | | VSH Out to Out Measurements | | CA Out to Out Measurements |
|------|-------------------------------|------|--------------------------------|------|-------------------------------|
| 3020 | 35-1/2" x 23-1/2" | 2030 | 23-1/2" x 35-1/2" | 2040 | 23-1/2" x 47-1/2" |
| 3030 | 35-1/2" x 35-1/2" | 3030 | 35-1/2" x 35-1/2" | | |
| 3040 | 35-1/2" x 47-1/2" | 3040 | 35-1/2" x 47-1/2" | | |
| 4020 | 47-1/2" x 23-1/2" | | | | |
| 4030 | 47-1/2" x 35-1/2" | | | | |
| 4040 | 47-1/2" x 47-1/2" | | | | |
| 5040 | 59-1/2" X 47-1/2" | | | | |
| | CT Out to Out | | | | |
| 30 | 35-1/2" Half-Circular | | | | |
| 40 | 47-1/2" Half-Circular | | | | |

Special Sizes can be ordered.* Multiple windows can be mull together in the factory - special order.

* max. size with grids = 35 sq. ft.

Due to Plyco Corporation's ongoing commitment to product improvement, we reserve the right to change without notice, product specifications and availability.