PLYCO®

Everlast

20 Series

DATA SHEET

EVERLAST INSULATED COMMERCIAL WALK DOOR, PRE-HUNG WITH HEADER AND THRESHOLD
PRE-HUNG 4 WAY UNIVERSAL IS STANDARD

Physical Characteristics

Special Sizes Not Available in this Series.

Sizes	2/6 x 6/8	2/8 x 6/8	3/0 x 6/8	3/6 x 6/8	4/0 x 6/8	Dbl. 6/0 x 6/8	Dbl. 8/0 x 6/8
			3/0 x 7/0	3/6 x 7/0	4/0 x 7/0	Dbl. 6/0 x 7/0	Dbl. 8/0 x 7/0

Overall Dimensions	a) For correct out to out dimensions see Data Sheet DO-1. 3/0 x 6/8 = 39 7/8" x 81 3/8". b) For Rough Opening dimensions, use dimensions (above - a) and add 3/8" to width and 3/8" to height. Example: R.O. 3/0 x 6/8 = 39 7/8" + 1/2" Width x 81-3/8" + 3/8" Height = 40 3/8" x 81 3/4" Rough Opening
Mullion / Astragal	Double doors have attached astragal on the inactive panel of the pair - shipped knocked-down. Hinges are attached to jambs. Manual head and foot bolt concealed in the astragal.
Hinges	(3) 4" x 4" Stainless Steel NRP hinges are standard, Ball-Bearing stainless steel on 4/0 sizes.
DOOR PANEL	
Thickness	1 3/4"
Skin	Smooth 24 ga. galvanized steel painted finish 3068 available in 6-panel or X-Buck styles.
Edges	Rolled edge in aluminum core rails.
Blocking	HDPE lock reinforcing structure, optional steel closer blocking. Special lock blocking is available.
Insulation	Panel R-13 (u= .077)
Embossing	3/0 x 6/8 only - Six panel style, X-Buck style.
Colors	Polar White only finish paint.
Lock	Face Prep Standard with 2 1/8" lockset bore, 2 3/4" backset. Non-bored is optional.
Deadbolt	Optional face bore and edge prep for deadbolt, dbl. notch latchguard available as an option.
Sweep	Durable Alcryn bulb & fin sweep.
Lite Kits	1-LI-2 20" x 24" Insulated 1-LA-2 20" x 24" Single glazed 1-LE-2 16" x 16" Insulated 1-LB-2 22" x 36" Insulated 1-LU-2 4" x 48" Single glazed 9-LB-2 22" x 36" Insulated with 9-Lite internal grids Other glass sizes are available - lite kits listed above are most common.
JAMB	
Type	PREHUNG 16 ga. galv. steel - Flush plain doors are universal swing with dbl. contact weatherstrip.
Frame Depths	3 1/2" only. Reveal is 1-7/8"
Hinge Preps	Face mounted with concealed edge.
Anchors	Standard frame screws, optional masonry wall clips.
Threshold	Aluminum, painted, universal. ADA threshold is available. Dedicated swing option is avaialble.

Due to Plyco Corporation's ongoing commitment to product improvement, we reserve the right to change without notice, product specifications and availability.