



# 95EV Series

## DATA SHEET

EVERLAST INSULATED UTILITY WALK DOOR, PRE-HUNG WITH HEADER AND THRESHOLD  
PRE-HUNG 4 WAY UNIVERSAL IS STANDARD

### Physical Characteristics    Special Sizes Not Available in this Series.

Sizes	2/6 x 6/8	2/8 x 6/8	3/0 x 6/8	3/6 x 6/8	4/0 x 6/8	DbL. 6/0 x 6/8	DbL. 8/0 x 6/8
			3/0 x 7/0	3/6 x 7/0	4/0 x 7/0	DbL. 6/0 x 7/0	DbL. 8/0 x 7/0

Overall Dimensions    a)      For correct out to out dimensions see Data Sheet DO-3 dated 11-2017.

b)      For Rough Opening dimensions, use dimensions (above - a) and add 1/2" to width and 3/8" to height.

Example: R.O. 3/0 x 6/8 = 38" + 1/2" Width x 81-3/8" + 3/8" Height = 38-1/2" x 81-3/4" Rough Opening

Mullion / Astragal      Double doors have attached astragal on the inactive panel of the pair - shipped knocked-down. Hinges are attached to jambs. Manual head and foot bolt concealed in the astragal.

Hinges      (3) 4" x 4" zinc plated fixed-pin hinges are standard, SS/NRP available as an option.

#### DOOR PANEL

Thickness      1 3/4"

Skin      Smooth 26 ga. galvanized steel painted finish Polar White available in 6-panel.

Edges      Rolled edge in aluminum core rails.

Blocking      HDPE lock reinforcing structure, optional patented heavy duty aluminum closer blocking.  
Special lock blocking is available.

Insulation      Panel R-13 (u= .077)

Embossing      3/0 x 6/8 only - Six panel style.

Colors      Polar White and Chocolate finish paint.

Lock      Face Prep Standard with 2 1/8" lockset bore, 2 3/4" backset. Non-bored is optional.

Deadbolt      Optional face bore and edge prep for deadbolt, narrow line latchguard available as an option.

Sweep      Durable Alcryn bulb & fin sweep.

Lite Kits	1-LI-2  20" x 24" Insulated	1-LA-2  20" x 24" Single glazed
	1-LE-2  16" x 16" Insulated	1-LB-2  22" x 36" Insulated
	1-LU-2  4" x 48" Single glazed	9-LB-2  22" x 36" Insulated with 9-Lite internal grids

Other glass sizes are available - lite kits listed above are most common.

#### JAMB

Type      PREHUNG 16 ga. galv. steel - Flush plain doors are universal swing with Q-Lon kerf-weatherstrip.

Hinge Preps      Face mounted with concealed edge.

Anchors      Standard frame screws, optional masonry wall clips.

Threshold      Aluminum, painted, universal. Double doors include full header with Q-Lon kerf seal.