

DATA SHEETS

INSULATED WALK DOOR, PRE-HUNG WITH HEADER AND THRESHOLD PRE-HUNG 4 WAY UNIVERSAL IS STANDARD

Physical Characteristics

SIZES - Single Doors: Width for single door is limited to 4' (40), height is limited to 7' (70) tall. Doors can be made in any size within these limitations.

Double Doors: Can be manufactured up to 8' (80) wide and 7' (70) tall. Double door has astragal attached to inactive panel, has head and foot bolt included in astragal. Right side active panel is standard, may request left side active.

- **COLORS -** Polar White, Chocolate (Available up to 30 width and 68 height). Also available with a mil-finish jamb and panel perimeter with a Polar White skin.
- **JAMB -** 3-1/2" aluminum with wool pile weather seals. Jamb is available in mil-finish, polar white, and chocolate. Nailing fin is available as an outswing door in Polar White and mil-finish.
- **HINGES -** 4" x 4" zinc removable pin hinges are standard. (3) 4" x 4" stainless steel fixed pin hinge is available as an option.
- **DOOR PANEL** Aluminum frame surrounds the panel and captures the steel skin. 1-1/2" thick panel is a rolled edge style. The panel core polyurethane injected foam. Weather seal at the top and bottom. Standard comes bored for lockset at 2-3/4" setback with rectangular latch plate prep.
- BLOCKING: Blocked and drilled for lockset standard. When latch quard is ordered, door is blocked and guard is installed over lockset. When deadbolt is ordered, door is blocked and prepped for deadbolt. When panic hardware is ordered, door is prepped at the vertical center point of door.

SKIN TYPE: Panels under 48" (40) in width - 32 gauge embossed steel skin is standard. Panels 48" (40) in width - 29 gauge embossed steel is standard. Fiberglass (.06" textured white) and aluminum (.019" embossed white) skins available as an option.

THRESHOLD - Aluminum thresholds are used with this door series. Standard is not handicapped approved.

LITE KITS - Lites often requested are:

1 I A 20x24 no grids

1 LU 4"x48 no grids.

Additional lite kits are available, see the accessory pages for other lite sizes.

HARDWARE - See accessory pages for listing of hardware available.