

Trim Line WINDOWS

COMMERCIAL GRADE THERMAL PANE VINYL FRAME WINDOWS

DESIGNED SPECIFICALLY FOR THE METAL CLAD CONSTRUCTION INDUSTRY



Horizontal Slider-CV150 Also Available: Single Hung-CV112

The One Hundred Series

CV100

High Impact uPVC Vinyl

PLYCO
CORPORATION

Elkhart Lake, WI 53020

USA
800-558-5895
Fax 800-257-5926

INTERNATIONAL
920-876-3611
Fax 920-876-3527

Commercial Vinyl Window

At last, a window designed with the builder in mind!

Our new Commercial Grade Thermal Pane Vinyl Window has all the features you're looking for in a quality window and easier installation all at an economical price! This window is installed and the exterior metal sheeting fitted before the snap-in "J" trim is attached to the window frame - making installation much less of a problem than fitting the exterior sheeting behind existing "J" trim. The 2 1/2" all welded frame construction and multi-chambered uPVC profiles increase window strength and performance, reduce noise, are energy efficient and provide years of maintenance-free beauty. Available in white in single hung and horizontal slider styles.



FEATURES AND BENEFITS

1 Optional Snap-in "J" Trim

- Easier to fit sheeting around window
- Eliminates hammer-damaged "J" trim during installation
- Can substitute colored metal "J" if desired

2 Glazing

- Standard 3/4" sealed thermal pane glass
- Equal glass sizes expand exterior view; pleasing good looks
- Replaceable from the interior

3 Integral Fully Weatherstripped Interlock and Lift Rail

- Withstands greater wind load pressures
- Prevents sash sag
- Superior seal keeps your building free from drafts

4 All Welded Frame

- Increases frame strength and window performance
- Energy efficient multi-chambered profile
- Clean, crisp, maintenance-free good looks

5 2-1/2" Master Frame

- Triple seal sill
- Internal water drainage
- Ultra-high molecular weight polyethylene plastic; high wear, low maintenance
- Designed to function in hot or cold climates without cracking or having excess expansion or contraction of components

Standard Sizes

Horizontal Slider

- CV-W3020HS R.O. 36" X 24"
- CV-W3030HS R.O. 36" X 36"
- CV-W3040HS R.O. 36" X 48"
- CV-W4020HS R.O. 48" X 24"
- CV-W4030HS R.O. 48" X 36"
- CV-W4040HS R.O. 48" X 48"
- CV-W5030HS R.O. 60" X 36"
- CV-W5040HS R.O. 60" X 48"
- CV-W6040HS R.O. 72" X 48"

Vertical Single Hung

- CV-W2030VSH R.O. 24" X 36"
- CV-W3030VSH R.O. 36" X 36"
- CV-W3040VSH R.O. 36" X 48"

Above dimensions represent rough opening sizes. Out-to-Out dimensions (less removable nailing flange) are actually 1/2" less than stated rough opening.