



RIDGE VENTS

DATA SHEET

Description

A number of styles and designs of Ridge Vents are manufactured by Plyco. Stocked units are pre-finished 29 gauge steel. We also carry paint-ready sheet steel to produce custom shop-painted colors.

Physical Characteristics

- MATERIAL** Stocked units are pre-finished 29 ga. Steel.
- COLORS** Plyco Ridge Vents are available in most roll former steel colors. Call Plyco for color options & availability. We also carry paint-ready sheet steel to produce custom shop-painted colors.
- STYLES: MWE-100** Low profile (2-3/4" above roof peak) 10 ft. vent with 12 square inches of free air flow per lineal foot. It has a closed top with 1/2" opening on each side.
- MW-100-25** Low profile (3" above roof peak) 10 foot vent with open top for additional air flow (30 square inches per lineal foot). 2-3/4" throat with a 3-3/4" flange and 14-1/2" overall width. Designed to exhaust air out of the attic or building.
- MW-100-25** Low profile (3" above roof peak) 10 foot vent with Quick Vent foam.
- MW-100-35** Similar design as the MW100-25 with 36 square inches of free air flow per lineal foot. The vent stands 4-1/2" above the roof peak and has a 3-1/2" throat.
- FMW-100-35** This vent is constructed with a translucent fiberglass diverter to bring in natural light at the ridge. All other features are similar to the MW-100-35.
- MW-CRV-904** Large vent of 24 gauge steel designed for buildings that require increased air flow. The vent is 4' in length, stands 13-1/4" above the roof peak and has a 9" throat area.
- MW-CRV904-WD** Similar to the MW-CRV-904, with damper for control of air flow.
- MW-CRV910-WS** Large vent of 24 gauge steel designed for buildings that require increased air flow. The vent is 10' in length, stands 13-1/4" above the roof peak and has a 9" throat area.
- NT-AF52** Corrosion resistant molded fiberglass vent with a 11-1/4" x 40" throat. The unit is 54" long and 33-1/2" in width, including the flanges. Includes polyethylene netting to prevent bird entry.
- NT-AF52DAMP** Similar to the NT-AF4, with damper for control of air.
- NT-AFLP** Corrosion resistant molded fiberglass vent with a 4" throat. The unit is 10' 6" long and 15-1/4" in width, including the flange. Includes polyethylene netting to prevent bird entry. Dampers are not available on this unit.
- RCV-PQV-BOX** Quickvent reticulated foam 2" x 1-1/4" x 10' with adhesive one side. Material allows air to flow, and compresses very easily at ribs of roof sheet metal. Fills up to a 1" continuous gap.
- RCV-PQV-SKID** Quickvent reticulated foam full skid / pallet quantities.

Due to Plyco Corporation's ongoing commitment to product improvement, we reserve the right to change without notice, product specifications and availability.

VENTS-1