



# AND Windows

## Andersen 100 Series Window

### DATA SHEET

ENERGY SAVING & ENVIRONMENTALLY FRIENDLY WINDOW  
 FIBREX MATERIAL FRAME - 40% RECYCLED FIBER - LEED QUALIFIED  
 INSULATED GLASS WITH LO-E AND ARGON FILL  
 3-1/4" FRAME DEPTH WITH NAILING FLANGE 1-3/8" SETBACK

#### Physical Characteristics

<b>STYLES - HS</b>	Horizontal Single Slider with Nailing Flange
<b>VSH</b>	Vertical Single Hung with Nailing Flange
<b>VSH2</b> (Special Order)	Vertical single Hung Double with Nailing Flange
<b>CA L or R</b>	Casement Single (Left or Right Swing) with Nailing Flange
<b>CA2</b> (Special Order)	Casement Double with Nailing Flange
<b>FL</b> (Special Order)	Fixed Lite Picture Window with Nailing Flange
<b>CT</b>	Half-Circular Top

**COLORS** - Stock Exterior White, Stock Exterior Hickory Moss. All Windows - Interior White

**GLASS** - 5/8" Double Sealed Insulated Glass - Lo-E with Argon Fill is Standard.

Options Available: Grids Color Exterior, White Interior.  
 Field mulling kit.

**SIZES** - Standard Sizes are

	HS Out to Out Measurements		VSH Out to Out Measurements		CA Out to Out Measurements
3020	35-1/2" x 23-1/2"	2030	23-1/2" x 35-1/2"	2040	23-1/2" x 47-1/2"
3030	35-1/2" x 35-1/2"	3030	35-1/2" x 35-1/2"		
3040	35-1/2" x 47-1/2"	3040	35-1/2" x 47-1/2"		
4020	47-1/2" x 23-1/2"				
4030	47-1/2" x 35-1/2"				
4040	47-1/2" x 47-1/2"				
5040	59-1/2" X 47-1/2"				
	CT Out to Out				
30	35-1/2" Half-Circular				
40	47-1/2" Half-Circular				

Special Sizes can be ordered.\* Multiple windows can be mulled together in the factory - special order.

\* max. size with grids = 35 sq. ft.

Due to Plyco Corporation's ongoing commitment to product improvement, we reserve the right to change without notice, product specifications and availability.