



20 Series

DATA SHEET



EVERLAST INSULATED COMMERCIAL WALK DOOR, PRE-HUNG WITH HEADER AND THRESHOLD
PRE-HUNG 4 WAY UNIVERSAL IS STANDARD

Physical Characteristics Special Sizes Not Available in this Series.

Sizes	2/6 x 6/8	2/8 x 6/8	3/0 x 6/8	3/6 x 6/8	4/0 x 6/8	Dbl. 6/0 x 6/8	Dbl. 8/0 x 6/8
			3/0 x 7/0	3/6 x 7/0	4/0 x 7/0	Dbl. 6/0 x 7/0	Dbl. 8/0 x 7/0

Overall Dimensions a) For correct out to out dimensions see Data Sheet DO-1. 3/0 x 6/8 = 39 7/8" x 81 3/8".

b) For Rough Opening dimensions, use dimensions (above - a) and add 1/2" to width and 3/8" to height.

Example: R.O. 3/0 x 6/8 = 39 7/8" + 1/2" Width x 81-3/8" + 3/8" Height = 40 3/8" x 81 3/4" Rough Opening

Mullion / Astragal Double doors have attached astragal on the inactive panel of the pair - shipped knocked-down with full header. Hinges are attached to jambs. Manual head and foot bolt concealed in the astragal. Astragal is non-detachable.

Hinges (3) 4" x 4" Stainless Steel NRP hinges are standard, Ball-Bearing stainless steel on 4/0 sizes.

DOOR PANEL

Thickness 1 3/4"

Skin Smooth 24 ga. galvanized steel painted finish. 3/0 x 6/8 available in 6-panel or X-Buck styles. Edges Rolled edge in aluminum core rails.

Blocking HDPE lock reinforcing structure, optional steel closer and panic bar blocking. Special lock blocking is available.

Insulation Panel R-13 foamed.

Embossing 3/0 x 6/8 only - Six panel style, X-Buck style.

Colors Polar White , Hickory Moss, Chocolate Brown, Bronze

Lock Face Prep Standard with 2 1/8" lockset bore, 2 3/4" backset. Non-bored is optional.

Deadbolt Optional face bore and edge prep for deadbolt, dbl. notch latchguard available as an option.

Sweep Durable Alcryn bulb & fin sweep.

Lite Kits	1-LI-2 20" x 24" Insulated	1-LT-2 7" x 36" Insulated
	1-LE-2 16" x 16" Insulated	1-LB-2 22" x 36" Insulated
	15-L-2 22" x 60" Insulated 15 Lite	9-LB-2 22" x 36" Insulated with 9-Lite internal grids

Other glass sizes are available - all glass is tempered, CPSC 16CFR-1201 Cat. II. Lo-E glass is special order.

JAMB

Type PREHUNG 16 ga. galv. steel - Flush plain doors are universal swing with dbl. contact weatherstrip.

Frame Depths 3 1/2" only. Reveal is 1-7/8"

Hinge Preps Face mounted with concealed edge.

Anchors Standard frame wood screws, optional self drilling steel framing screws, optional masonry wall clips.

Threshold Aluminum, painted, universal. ADA threshold is available. Dedicated swing option is available.