



DESIGNER

Series

DOOR AND FRAME COLOR OPTIONS

BUILD YOUR DOOR

Step 1:
Choose Door Panel Color
(Standard or Additional)

Step 2:
Choose Frame Color
(Stock Colors or Painted Frame)

STEP 1 - DOOR PANEL COLORS



Sizes Available:
Single Door Up To 3068/3070 & Double Door Up To 6068/6070


STANDARD COLORS




Polar White - 100




Black - 816



Hickory Moss - 603




Bronze - 250




Chocolate - 242

20 Only


TIER 1 COLORS



Ash Gray - 112




Satin Silver - 114




Light Stone - 308



Rural Red - 501



Quaker Gray - 806



Evergreen - 630



Earth Brown - 209


ADDED DOOR PRICE
Approximate added price
to 3068/6068 below.

Single Door
Double Door


TEXTURED COLORS



Ash Gray - 112T



Quaker Gray - 806T



Light Stone - 308T



Red - 501T




Black - 826T


TIER 2 COLORS



Red - 504



Charcoal - 802



Terratone - 349



Black (Matte) - 826

ADDED DOOR PRICE
Approximate added price
to 3068/6068 below.

Single Door Double Door

STEP 2 - FRAME COLORS



PICK 1 OF THE 5 STANDARD COLORS




Polar White - 100




Black - 816



Hickory Moss - 603



Bronze - 250



Chocolate - 242

No Additional Charge

20 Only

OR

PAINT FRAME TO MATCH

Single Frame

Double Frame

DOOR AND FRAME COLOR OPTIONS

SERIES 20



FEATURES

- 24 Gauge Everlast steel panel, 1 3/4" thick with fully-rolled edges
- 3 1/2" 16 Gauge Steel Frame
- Full header with dedicated inswing or outswing threshold provides high performance (Black only available with full header option).
- Stainless steel hinges standard
- Resilient, flexible weather stripping on jamb allows for greater leak protection
- Jamb includes hinge and strike recess and counter sunk mounting holes for smooth installation
- HDPE composite lock block and deadbolt prep standard
- ADA compliant accessible threshold is optional
- Individually cartoned and packaged to help prevent shipping damage
- Florida Building Code Certification

SERIES 92



FEATURES

- Complete thermal-break door system
- 24 Gauge Everlast hot dipped galvanized steel panel, 1 3/4" thick with fully-rolled edges
- Thermally-broken, one-piece aluminum frame for added structural strength. Stronger & Lighter!
- Energy-saving solid polyurethane insulating door core with an R-13 value
- 4 1/2"x4 1/2" stainless steel (NRP) hinges
- HDPE composite lock block, deadbolt prep and steel closer reinforcements are standard
- Individually cartoned and packaged to help prevent shipping damage
- Available in 3 frame depths: 4 1/4", 6 1/4", 8 1/4"
- NFRC 100 Tested U Value - .24 (flush)
- Florida Building Code Certification