

## SERIES 31

# INSULATED UTILITY DOOR



### DOOR PANEL

- 24 Gauge hot dipped galvanized steel panel, 1 1/2" thick
- Energy-saving solid Polyurethane insulating core with an R-11 value
- Three (3) mortised 4"x4" stainless steel hinges with heavy 10-gauge steel hinge reinforcements
- Composite lock and deadbolt reinforcement structure
- Available with any Plyco window kit -see Plyco Lite Kit page
- 3068 available with Cross Buck and Six Panel design
- Individually cartoned and packaged to help prevent shipping damage

### SPLIT JAMB

- Unique frame design for use in exterior metal applications
- Adjustable jamb widths 3 1/2" to 4 3/4"
- Pre-finished painted aluminum jambs
- Attractive self-flashing jamb allows for easy, time-saving installation



# PLYCO Series 31 Door

SIZES	2668-2868-3068-3668-4068-5068-6068-7068-8068		
OVERALL DIMENSIONS	3068: 37 1/4" x 81" (recommended rough opening 37 3/4" x 81 3/4")		
MULLION/ASTRAGAL	6'x8' doors have attached astragal		
HINGES	(3) 4"x4" high-quality stainless steel (NRP) fixed-pin hinges		
THRESHOLD	Aluminum		
DOOR PANEL			
THICKNESS	1 1/2"		
SKIN	Smooth 24 GA. hot dipped galvanized steel		
EDGES	Framed		
BLOCKING	Composite lock reinforcement structure, optional closure block		
INSULATION	Solid polyurethane core		
R-VALUE	R-11.5 (u=.087)		
EMBOSSING	3068 - Cross buck & six panel		
COLORS	Standard polar white only		
LOCK FACE PREP	STD with lockset bored at 2 1/8" bore at a backset of 2 3/4"		
DEAD BOLT	Dead bolt prep is optional		
SWEEP	Heavy-duty, slide-on fin & bulb sweep (replacable)		
LITE KITS	1-LU 4 x 48	1-LE 16 x 16	1-LA 20 x 24
SEE LITE KIT PAGE	1-LI 20x24	1-LB 22 x 36	1-LL 22 x 60
FOR ADDITIONAL LITES	1-LW 16 x 16 w/grid	9-LB 22 x 36 w/grid	15-LB 22 x 60 w/grid

## JAMB

<b>TYPE</b>	Pre-Hung
<b>MATERIAL</b>	Aluminum
<b>FEATURES</b>	Adjustable 3 1/2" to 4 3/4"
<b>FLASHING</b>	Self Flashing
<b>HINGE</b>	Heavy 10 gauge steel
<b>REINFORCEMENT</b>	
<b>THERMAL BREAK</b>	N/A

## LAB TESTS

THERMAL PERFORMANCE R-13 (U=.077)

Because of its ongoing commitment to product improvement, Plyco Corporation reserves the right to change, without notice, product specifications, availability, prices and conditions of sale.

**PLYCO**  
CORPORATION  
PO BOX Q • ELKHART LAKE, WI 53020

**www.plyco.com 800/558-5895 FAX: 800/257-5926**  
**INTERNATIONAL 920/876-3611 FAX: 920/876-3527**

WINDOWS • WALK DOORS • WALL VENTS • RIDGE VENTS  
SLIDING DOOR TRACK • SLIDE DOOR RAILS • PLY-FOIL INSULATION  
HORSE STALLS • FASTENERS & CLOSURES • SPECIALTY PRODUCTS