



## 85EV Series DATA SHEET

## EVERLAST INSULATED UTILITY WALK DOOR, PRE-HUNG WITH HEADER AND THRESHOLD PRE-HUNG 4 WAY UNIVERSAL IS STANDARD

Physical Characteristics Special Sizes Not Available in this Series.	
Sizes 2/6	x 6/8 2/8 x 6/8 3/0 x 6/8 3/6 x 6/8 4/0 x 6/8 Dbl. 6/0 x 6/8 Dbl. 8/0 x 6/8
	3/0 x 7/0 3/6 x 7/0 4/0 x 7/0 Dbl. 6/0 x 7/0 Dbl. 8/0 x 7/0
Overall Dimens	sions a) For correct out to out dimensions see Data Sheet DO-1 dated 09-2019.
b) For Ro	ugh Opening dimensions, use dimensions (above - a) and add 1/2" to width and 3/8" to height. Example:
R.O. 3/0 x 6/8 = 38 1/8" + 1/2" Width x 81-3/8" + 3/8" Height = 38-5/8" x 81-3/4" Rough Opening	
Mullion / Astra	gal Double doors have attached astragal on the inactive panel of the pair - shipped knocked-
	down. Hinges are attached to jambs. Manual head and foot bolt concealed in the astragal.
Hinges	(3) 4" x 4" 304 SS - NRP are standard.
DOOR PANEL	
Thickness	1 3/4"
Skin	Smooth 24 ga. galvanized steel painted finish Polar White available in 6-panel.
Edges	Rolled edge in aluminum core rails.
Blocking	HDPE lock reinforcing structure, optional 16 ga. steel closer blocking.
	Special lock blocking is available.
Insulation	Panel R-12
Embossing	3/0 x 6/8 only - Six panel style.
Colors	Polar White finish paint. Chocolate brown available at an extra charge.
Lock	Face Prep Standard with 2 1/8" lockset bore, 2 3/4" backset. Non-bored is optional.
Deadbolt	Optional face bore and edge prep for deadbolt, narrow line latchguard available as an option.
Sweep	Durable Alcryn bulb & fin sweep.
Lite Kits 1-LI-2	20" x 24" Insulated1-LA-220" x 24" Single glazed
	1-LE-2 16" x 16" Insulated 1-LB-2 22" x 36" Insulated
	1-LU-24" x 48" Single glazed9-LB-222" x 36" Insulated with 9-Lite internal grids
	Other glass sizes are available - lite kits listed above are most common.
JAMB	
Туре	PREHUNG 16 ga. galv. steel - Flush plain doors are universal swing with Q-Lon kerf-weatherstrip.
Hinge Preps	Face mounted with concealed edge.
Anchors	Standard frame screws, optional masonry wall clips.
Threshold	Aluminum, painted, universal. Dedicated swing style threshold for water resistance is available.
Double doors include full header with Q-Lon kerf seal.	