



95EV Series

DATA SHEET

EVERLAST INSULATED UTILITY WALK DOOR, PRE-HUNG WITH HEADER AND THRESHOLD PRE-HUNG 4 WAY UNIVERSAL IS STANDARD

Physical Characteristics Special Sizes Not Available in this Series.

Sizes 2/6 x 6/8 2/8 x 6/8 3/0 x 6/8 3/6 x 6/8 4/0 x 6/8 Dbl. 6/0 x 6/8 Dbl. 8/0 x 6/8

 $3/0 \times 7/0$ $3/6 \times 7/0$ $4/0 \times 7/0$ Dbl. $6/0 \times 7/0$ Dbl. $8/0 \times 7/0$

Overall Dimensions a) For correct out to out dimensions see Data Sheet DO-3 dated 11-2017.

b) For Rough Opening dimensions, use dimensions (above - a) and add 1/2" to width and 3/8" to height.

Example: R.O. $3/0 \times 6/8 = 38^{\circ} + 1/2^{\circ}$ Width $\times 81-3/8^{\circ} + 3/8^{\circ}$ Height $= 38-1/2^{\circ} \times 81-3/4^{\circ}$ Rough Opening

Mullion / Astragal Double doors have attached astragal on the inactive panel of the pair - shipped knocked-

down. Hinges are attached to jambs. Manual head and foot bolt concealed in the astragal.

Hinges (3) 4" x 4" zinc plated fixed-pin hinges are standard, SS/NRP available as an option.

DOOR PANEL

Thickness 1 3/4"

Skin Smooth 26 ga. galvanized steel painted finish Polar White available in 6-panel.

Edges Rolled edge in aluminum core rails.

Blocking HDPE lock reinforcing structure, optional patented heavy duty aluminum closer blocking.

Special lock blocking is available.

Insulation Panel R-13 (u = .077)

Embossing 3/0 x 6/8 only - Six panel style.

Colors Polar White and Chocolate finish paint.

Lock Face Prep Standard with 2 1/8" lockset bore, 2 3/4" backset. Non-bored is optional.

Deadbolt Optional face bore and edge prep for deadbolt, narrow line latchguard available as an option.

Sweep Durable Alcryn bulb & fin sweep.

Lite Kits 1-LI-2 20" x 24" Insulated 1-LA-2 20" x 24" Single glazed

1-LE-2 16" x 16" Insulated 1-LB-2 22" x 36" Insulated

1-LU-2 4" x 48" Single glazed 9-LB-2 22" x 36" Insulated with 9-Lite internal grids

Other glass sizes are available - lite kits listed above are most common.

JAMB

Type PREHUNG 16 ga. galv. steel - Flush plain doors are universal swing with Q-Lon kerf-weatherstrip.

Hinge Preps Face mounted with concealed edge.

Anchors Standard frame screws, optional masonry wall clips.

Threshold Aluminum, painted, universal. Double doors include full header with Q-Lon kerf seal.

Due to Plyco Corporation's ongoing commitment to product improvement, we reserve the right to change without notice, product specifications and availability.

DR95EV-001 rev 11-15-2017

DO-30