



99E Series



DATA SHEETS

EVERLAST INSULATED UTILITY WALK DOOR, PRE-HUNG WITH HEADER AND THRESHOLD
ROLLED EDGE PRE-HUNG 4 WAY UNIVERSAL IS STANDARD

Physical Characteristics **Special Sizes Not Available in rolled edge style.**

Sizes	2/6 x 6/8	2/8 x 6/8	3/0 x 6/8	3/6 x 6/8	4/0 x 6/8	Dbl. 6/0 x 6/8	Dbl. 8/0 x 6/8
			3/0 x 7/0	3/6 x 7/0	4/0 x 7/0	Dbl. 6/0 x 7/0	Dbl. 8/0 x 7/0

Overall Dimensions a) For correct out to out dimensions see Data Sheet DO-1
 b) For Rough Opening dimensions, use dimensions (above - a) and add 1/2" to width and 3/8" to height. Example: R. O. 3/0 x 6/8 = 37-1/2" + 1/2" Width x 81-3/8" + 3/8" Height = 38" x 81-3/4" Rough Opening

Mullion / Astragal Double doors have attached astragal on the inactive panel of the pair - shipped knocked-down. Hinges are attached to jambs. Manual head and foot bolt concealed in the astragal.

Hinges (3) 4" x 4" zinc plated loose pin hinges are standard. SS/NRP available as an option.

DOOR PANEL

Thickness 1 3/4"

Skin Smooth 26 ga. galv. steel painted finish Polar White

Edges Rolled edge in aluminum core rails.

Blocking HDPE lock reinforcing structure, optional 16 ga. steel closer blocking.
 Special lock blocking is available. For Latchguard - add nailing fin option to engage Latchguard pin.

Insulation Panel R-13 (u= .077)

Embossing 3/0 x 6/8 only - Six panel style Polar White only.

Colors Polar White

Lock Face Prep Standard with 2 1/8" lockset bore, 2 3/4" backset. Non-bored is optional

Deadbolt Optional face bore and edge prep for deadbolt, latchguard available as an option.

Sweep Durable PVC bulb & double fin sweep

Lite Kits	1-LI-2 20" x 24" Insulated	1-LA-2 20" x 24" Single glazed
	1-LE-2 16" x 16" Insulated	1-LB-2 22" x 36" Insulated (3/0 Doors and larger only.)
	1-LU-2 4" x 48" Single glazed	9-LB-2 22" x 36" Insul. 9-Lite (3/0 Doors and larger only.)

Other glass sizes are available - lite kits listed above are most common.

JAMB

Type PREHUNG Aluminum - Flush plain doors are universal swing with heavy pile weatherstrip.

Frame Depths 3 1/2" only. Optional slide in Nailing Flange (99NF) for either in-swing or out-swing (changeable).

Hinge Preps Face mounted with concealed edge.

Colors Polar White, or Mill Finish

Anchors Standard zinc plated & corrosion resistant coated frame screws. Optional nailing fin for in-swing or out-swing. Threshold Aluminum, universal, painted.