99E Series

DATA SHEETS

EVERLAST INSULATED UTILITY WALK DOOR, PRE-HUNG WITH HEADER AND THRESHOLD
ROLLED EDGE PRE-HUNG 4 WAY UNIVERSAL IS STANDARD

Physical Characteristics

Special Sizes Not Available in rolled edge style.

Sizes	2/6 x 6/8	2/8 x 6/8	3/0 x 6/8	3/6 x 6/8	4/0 x 6/8	Dbl. 6/0 x 6/8	Dbl. 8/0 x 6/8
			3/0 x 7/0	3/6 x 7/0	4/0 x 7/0	Dbl. 6/0 x 7/0	Dbl. 8/0 x 7/0

Overall Dimensions
a) For correct out to out dimensions see Data Sheet DO-3
b) For Rough Opening dimensions, use dimensions (above - a) and add 1/2" to width and 3/8" to height. Example: R. O. 3/0 x 6/8 = 37-1/2" + 1/2" Width x 81-3/8" + 3/8" Height = 38" x 81-3/4" Rough Opening

Mullion / Astragal: Double doors have attached astragal on the inactive panel of the pair - shipped knocked-down. Hinges are attached to jambs. Manual head and foot bolt concealed in the astragal.

Hinges: (3) 4" x 4" zinc plated loose pin hinges are standard, SS/NRP available as an option.

DOOR PANEL

Thickness	1 3/4"
Skin	Smooth 27 ga. galv. steel painted finish Polar White or Chocolate Brown. Polar Aluminum optional.
Edges	Rolled edge in aluminum core rails.
Blocking	HDPE lock reinforcing structure, optional patented heavy duty aluminum closer blocking. Special lock blocking is available.
Insulation	Panel R-13 (u= .077)
Embossing	3/0 x 6/8 only - Six panel style
Colors	Polar White only finish paint.
Lock	Face Prep Standard with 2 1/8" lockset bore, 2 3/4" backset. Non-bored is optional
Deadbolt	Optional face bore and edge prep for deadbolt, latchguard available as an option.
Sweep	Durable Acryn bulb & fin sweep
Lite Kits	1-LI-2 20" x 24" Insulated; 1-LA-2 20" x 24" Single glazed; 1-LE-2 16" x 16" Insulated; 1-LB-2 22" x 36" Insulated; 1-LU-2 4" x 48" Single glazed; 9-LB-2 22" x 36" Insulated with 9-Lite internal grids. Other glass sizes are available - lite kits listed above are most common.

JAMB

Type	PREHUNG Aluminum - Flush plain doors are universal swing with heavy pile weatherstrip.
Frame Depths	3 1/2" only. Optional side in Nailing Flange (99NF) for either in-swing or out-swing (changeable).
Hinge Preps	Face mounted with concealed edge.
Anchors	Standard frame screws. Optional nailing fin for in-swing or out-swing. Optional slide in J-Trim kit.
Threshold	Aluminum, universal, painted.

Due to Plyco Corporation's ongoing commitment to product improvement, we reserve the right to change without notice, product specifications and availability.