

98FG

Fiberglass Panel

Series 98FG is a full fiberglass door designed for corrosive environments.



- Fiberglass Frame & Panel Perimeter
- Non-corrosive design
- Heavy 1/8" Thick Pebbled Fiberglass Reinforced Plastic Skin
- 2" Thick Foam Insulation
- Optional 16" x 16" & 20" x 24" Lite Kit Available
- Lockset, Deadbolt & Barn Style Latch (Sure-Latch) Options Available
- Stainless Steel Butt Hinge and Stainless Steel Strap Hinge Options Available
- Fiberglass Trim Kit Available



Quick Mount Nailing Flange

- Pre-Hung with fiberglass nailing flange
- Frame pre-drilled for mounting
- Available in right or left hand swing
- Quick installation with mounting screws supplied



Fiberglass Picture Frame

- No Paint
- UV Inhibitors
- Strong Impact Resistant
- Fiberglass Reinforced Plastic Skin
- Fiberglass Picture Frame makes custom size doors possible

PLYCO Series 98FG (Fiberglass Panel)

SIZES	<p>Single Doors: Available widths are 2/0 x 6/8, 2/6 x 6/8, 2/8 x 6/8, 3/0 x 6/8, 3/4 x 6/8, 3/8 x 6/8, 4/0 x 6/8, 3/0 x 7/0 3/8 x 7/0, and 4/0 x 7/0</p> <p>Double Doors: Standard sizes 6/0 x 6/8, 6/0 x 7/0, 7/0 x 7/0. Custom sizes available in any combination up to 7/4 x 7/0. Double door has astragal attached to inactive panel. Surface mounted head and foot bolts included. Right side active panel is standard, may request left side active.</p>
HINGES	(3) 6" 304 stainless steel strap T-hinges or (3) 4-1/2" 304 stainless steel butt (fixed pin) hinges are available.
THRESHOLD	Heavy rubber sweep is standard. Thermally broken, aluminum thresholds are available as an option. Standard is ADA approved.
BOTTOM SEALS	Heavy rubber sweep is standard. Heavy duty used without thresholds; (Optional) Aluminum holder with Alcryn PVC sweep with threshold
HARDWARE	Standard locksets and deadbolt options available. Heavy duty sure-latch optional
DOOR PANEL	
THICKNESS	1 15/16"
SKIN	.120" pebble-textured FRP (i.e., fiberglass) skin is standard. UV stabilized protective material is an available option.
EDGES	Fiberglass perimeter surrounds captures the fiberglass skin
BLOCKING	HD sure-latch blocking is standard. When deadbolt is ordered, door is blocked and bored for deadbolt. Closer blocking is optional. Special blocking may be ordered as an option.
INSULATION	Panel core is polyurethane injected foam
COLORS	Polar White
LOCK FACE PREP	Standard blocking for HD sure-latch. Panel can be ordered prepped for bored lockset.
DEADBOLT	Deadbolt hardware blocking is optional
SWEEP	Bulb & fin sweep with aluminum holder (used w/threshold) or heavy duty sweep (w/o threshold)
LITE KITS	<p>Thermal pane tempered glass lite is standard</p> <p>Lites often requested are:</p> <p>1 LE 16x16 no grids - Insulated</p> <p>1 LI 20x24 no grids - Insulated</p> <p>Additional lite kits are available, see the accessory pages for other lite sizes.</p>
JAMB	
TYPE	PREHUNG
MATERIAL	Non-corrosion pultruded fiberglass
FEATURES	Nailing flange and kerf weather seals.
FRAME DEPTHS	3 1/2"